

DPG (BIPC PRODUCT)

BANDAR IMAM PETROCHEMICAL COMPANY

PROPERTY	UNIT	METHOD	RESULT
<i>Density at 15.6 °C</i>	GR/CM3	D-4052	0.76-0.80
<i>R.V.P.</i>	PSIA	D-323	9.5 MAX
<i>Colour Saybolt</i>	--	D-156	12 MIN
<i>Total Sulphur</i>	PPM	D-3120	220 MAX
<i>Lead Content</i>	PPB	A.A.	10 MAX
<i>5PCT VOL RECOVERED</i>	°C	D-86	37MIN
<i>95PCT VOL RECOVERED</i>	°C	D-86	190 MAX
<i>Paraffin</i>	WT%	G.C.	TBR
<i>Olefins</i>	WT%	G.C.	TBR
<i>Naphthenes</i>	WT%	G.C.	TBR
<i>Aromatics</i>	WT%	G.C.	MIN 39
<i>DOCTOR TEST</i>	-----	-----	POSITIVE
<i>COPPER CORROSION</i>	-----	D 130	NO 1A

PORT RESTRICTIONS

LOAD RATE : 600 MT PER HOUR

JETTY RESTRICTIONS : L.O.A. 780 FEET WITH DRAFT 36 FEET