
 <p>National Petrochemical Company(NPC)</p>	Material Safety Data Sheet (MSDS) <i>According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1</i>	Page: 1 of 8
	Product Name:	Revision Number: 1
	Propane	
		Reactivity Flammability Health

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/ UNDERTAKING



Identification of the substance or preparation:	Alkanes (hydrocarbon) ,Aliphatic Hydrocarbon Molecular Weight: 44.097 Formula: C ₃ H ₈
Country of origin:	Iran (Islamic Republic of Iran)
CAS Number:	74-98-6
Synonyms:	Dim ethyl methane, LP-Gas, Liquefied Petroleum Gas, (LPG), Propane, Propyl Hydride.
Company/undertaking identification	National Petrochemical Company Iran Petrochemical Commercial Company (IPCC)
Manufacturer subcontractor:	None
Emergency phone number:	00982188881735
Contact email:	msds@petrochem-ir.net
Fax:	00982188839511
Association/Organization:	None
Use of the substance/Preparation:	None

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous substances:	Flammable liquid gas under pressure. Can form explosive mixtures with air. Can rapid suffocation. Liquid may cause freeze burn similar to frostbite.
Hazardous label(s):	Flammable gases
Toxicological characteristics:	May be harmful if inhaled. Asphyxiant at high concentration. CHS has not conducted specific toxicity tests on this product.
Substances present at a concentration below the minimum danger:	Propane may contain various percentages of these hazardous components, depending on the source of supply.
Other component:	

3. IDENTIFICATION OF HAZARDS

Risk phrases:	Flammable liquid gas under pressure. Can form explosive mixtures with air. Can rapid suffocation. Liquid may cause freeze burn similar to frostbite
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------

 <p>National Petrochemical Company(NPC)</p>	Material Safety Data Sheet (MSDS) <i>According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1</i>	Page: 2 of 8
	Product Name:	Revision Number: 1
	Propane	 <p>Reactivity Flammability Health</p>

Skin contact:

Direct contact with liquid propane can result in skin burns (frostbite). This material is a gas under normal atmospheric conditions thus no harmful effects from skin absorption are expected.

Eye contact:

Contact with liquid can cause momentary freezing followed by swelling and eye damage.

Inhalation :

High concentrations in confined spaces may limit oxygen available for breathing.

If swallowed:

This material is a gas under normal atmospheric conditions and ingestion not expected to occur in normal use.

Other information:

None

4. FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor NEVER induce swallowing in an unconscious person.

Skin contact :

Direct contact with liquid propane can result in skin burns (frostbite). This material is a gas under normal atmospheric conditions thus no harmful effects from skin absorption are expected.

In case of exposure by inhalation:

Person suffering from lack of oxygen should be removed to fresh air. If victim is not breathing, apply artificial respiration. Keep victim warm and get medical attention.

In case of splashes or contact with eyes:

Contact with liquid can cause freezing of tissue, flush thoroughly with lukewarm water for 15 minutes, occasionally lifting the upper and lower lids, until no evidence of chemical remaining. Get medical attention immediately.

Skin contact

In case of swallowing:



If swallowed, get immediate medical attention.

Note of physician:

5. FIRE FIGHTING MEASURES

Flammable class:

**Flash point : -104° C
Auto ignition: 467.7° C
UEL:2.1 LEL:9.5**

 <p>National Petrochemical Company(NPC)</p>	Material Safety Data Sheet (MSDS) <i>According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1</i>	Page: 3 of 8
	Product Name:	Revision Number: 1
	Propane	 <p>Reactivity Flammability Health</p>

Suitable extinguishing media:

Use dry chemical , co2 , water spray or fog for surrounding area .Do not extinguish gas fire unless the gas leak can be stopped . Use dry chemical or co2 for small fire. For large fire use water spray or fog, if there is no risk, move containers from fire area.

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:

Propane is easily ignited. It is heavier than air therefore can collect in low and confined areas, where there is an ignition source .Due to heat , pressure in a container can built up and container may rupture/explode if pressure relief devices should fail to function. Propane released from a properly functioning relief valve on an overheated container can also became ignited. Hazard combustion products isnot produced. Incomplete combustion may form carbon monoxide.

Special protective equipment for fire fighting :

In confined space use self contained breathing apparatus

Other information:

Prevent from entering sewers, basement and work pits, or any place where its accumulation can be dangerous.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Evacuate immediate area.

Environmental precautions:

Eliminate any possible sources of ignition and provide maximum ventilation. Shut off source of propane, if possible.

Methods for cleaning up and disposal:

Ventilate area.

Other information:



If leaking from container, or valve, contact your supplier.

7. HANDLING AND STORAGE

The regulations relating to storage premises apply to workshop where the product is handled :

Handling:

Valve protection caps must remain in place unless container is secured .Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing

 <p>National Petrochemical Company(NPC)</p>	Material Safety Data Sheet (MSDS) <i>According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1</i>	Page: 4 of 8
	Product Name:	Revision Number: 1
	Propane	 <p> Reactivity Flammability Health </p>

Storage:

regulator when connecting cylinder to lower pressure piping or systems .Do not heat cylinder to increase discharge rate of product from the cylinder . Use a check valve or trap in the discharge line to prevent hazardous back flow in the cylinder.

Cylinder should be separated from oxygen cylinders or other oxidizers by distance of 6 meters or by barrier of noncombustible materials at least 1.5 meters high having a fire resistance rating of at least half an hour. Full and empty cylinder should be segregated. Empty cylinder retains some residue and should be treated as if they were full. Use at first - in , first - out inventory system to prevent from full containers being stored for long periods of time Use only in well ventilated area.

Other information:

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values:

Propane :OSHA-TWA/PEL 1000 ppm

Butane : 800 ppm

Butane : ACGIH – TWA/PEL 800 ppm

Exposure controls:

Ensure adequate ventilation. Do not smoke while handling procedure.

Personal protective equipment:

Personal should never enter an area of high concentration without proper respiratory protection. Use a NIOSH approved self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode in oxygen deficient environments or exposure concentration is unknown or if immediately dangerous life or health (IDLH) exist.

A respiratory protection program that meets OSHA, s 29CFR1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respiratory, s use.

Eye protection:

Use face shield or chemical type goggles where contact with material may occur such as when changing valves hose ,etc.

Respiratory protection:

Positive pressure air line with mask or self



National Petrochemical
Company(NPC)

Material Safety Data Sheet (MSDS)

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Page: 5 of 8

Revision Number: 1

Product Name:

Propane



Reactivity
Flammability
Health

Hand protection:

Skin and body protection:

Health measures:

Environmental exposure controls:

contained breathing apparatus should be available for emergency use.

Use gloves when contact with liquid propane is possible.

Use protective clothing, face shield, and gloves when contact with liquid propane is possible.

Local exhaust ventilation is necessary to prevent accumulation above the TWA.

Use safety shoes, safety shower.

Exposure to containing more than 10% may cause dizziness. Exposure to atmospheres containing 8%-10% or less oxygen will bring about unconsciousness without warning, and so quickly that individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information:

Appearance (at 20°C):

Extremely flammable gas.

A colourless and tasteless gas at normal temperature. An odorant (ethyl mercaptan) has been added to provide a strong unpleasant odour. Should propane – air mixture reach the ethyl mercaptan concentration will be approximately 0.5 ppm in air.

Colour:

Colorless

Odour:

Unodorised propane has a slightly sweet odor. If an odorant has been added it will have a strong unpleasant odor.

PH (at 20°C):

Not applicable.

Boiling point/range (°C):

-42.04°C @ 1 atm

Flash point (°C):

-104° C

Flammability:

1.2% -9.5%

Auto-ignition temperature:

467° C

Explosive properties:

Can form explosive mixtures with air.

Oxidising properties:

1.5 at (21° C ,1 atm)

Vapour pressure (at 20°C):

200 psi max(at:73 °C)

Density (at 20°C):

1.87 kg/m3

Solubility (at 20°C) :

water solubility: Negligible

Viscosity (40°C):



.0074 c.p.

Evaporation rate:

N/A

Other information:

Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

 <p>National Petrochemical Company(NPC)</p>	<p align="center">Material Safety Data Sheet (MSDS)</p> <p align="center"><i>According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1</i></p>	<p>Page: 6 of 8</p>
	<p>Product Name:</p> <p align="center">Propane</p>	<p>Revision Number: 1</p>
		 <p>Reactivity Flammability Health</p>

10. STABILITY AND REACTIVITY



Stability:	Stable
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.
Material to avoid:	Avoid contact with incompatible materials, strong acids, Oxidizing agent such as chlorine (gas or liquid) and oxygen.
Hazardous decomposition products:	Under fir condition, can yield carbon monoxide, carbon dioxide, fume, smoke, aldehydes and other decomposition products.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Acute toxicity data is not applicable to this product.
Sub chronic – chronic toxicity:	Asphyxiant at high concentration. High concentrations in confined spaces may limit oxygen available for breathing.
Sensibilization:	None
Carcinogenicity:	This material has not been identified as a Carcinogen by NTP, IARC, or OSHA.
Reproductive effects:	None
Human experience:	None
Other information:	Propane is non-toxic and is a simple asphyxiant, however it dose have slight anesthetic properties and higher concentration may cause a narcotic effect and dizziness.

12. ECOLOGICAL INFORMATION

Ecotoxicity:	No known ecological damage caused by product.
Bio accumulative potential:	This product dose not contains any class 1 or 2 ozone depleting substances.
Mobility:	None
Persistence and degradability:	None
Other adverse effects:	No adverse ecological effects expected. The components of this mixture are not listed as marine pollutants by TDG regulations.

 <p>National Petrochemical Company(NPC)</p>	Material Safety Data Sheet (MSDS) <i>According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1</i>	Page: 7 of 8
	Product Name:	Revision Number: 1
	Propane	
		Reactivity Flammability Health

13. DISPOSAL CONSIDERATIONS

Disposal of product:

Do not attempt to dispose of residual or unused quantities. Return the cylinder to supplier. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous

Disposal of packaging:

Propane containers are special cylinder, and can be reused. Propane is non corrosive and may be used with any common structural material.

14. TRANSPORT INFORMATION

Land transport:

Container should be transported in a secure, upright position in a well ventilated vehicle.

Hazard class: 2.1

UN NO: 1978

DOT shipping name : propane

DOT shipping label: Flammable Gas

Classification above.

Classification above.

Classification above.

N/A

ADR/RID:

Packaging group:

Maritime transport:

Air transport:

15. REGULATORY INFORMATION

Hazardous label(s):



Class:2.1

Safety phrases:

S 9 , S 16 , S 33.

Risk phrases:

R 12

 National Petrochemical Company(NPC)	Material Safety Data Sheet (MSDS) According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1	Page: 8 of 8
	Product Name: Propane	Revision Number: 1
		 Reactivity Flammability Health

16. OTHER INFORMATION



The contents and format of this MSDS are in accordance with EEC Commission Directive 2001/58/EC

Disclaimer of liability:

The information in this MSDS was obtained from different sources, which National Petrochemical Company (NPC) and Iran Petrochemical Commercial Company (IPCC) believe, are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, National Petrochemical Company (NPC) and Iran Petrochemical Commercial Company (IPCC) do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.